



February 12, 2018

New Detector Tube from Uniphos Envirotronic Pvt. Ltd.

Description:	Hydrogen Sulfide -0.2%
Part Number:	D7000003
Measuring Range:	0.2-7 Vol%
Tests per Box:	10
Number of Strokes:	1 stroke, for 0.2-7 Vol%
Time per Stroke:	20-30 seconds
Discoloration:	Light blue to gray/black
Shelf Life:	2 years
Applications/Use:	<ul style="list-style-type: none"> • Hydrogen sulfide (H₂S) is naturally occurring in crude and natural gas. <ul style="list-style-type: none"> ○ Some natural gas has high volume percent levels of H₂S • The largest industrial source of H₂S is petroleum refineries where H₂S is converted into elemental sulfur or sulfuric acid. • The main use of H₂S is as a precursor to elemental sulfur. • Other sources of hydrogen sulfide include coke ovens in the steel industry, paper mills using the Kraft process, tanneries and sewage treatment facilities. • Hydrogen sulfide is naturally occurring due to the decomposition of animal and vegetable matter, and confined spaces such as manholes and manure pits should always be checked for its presence.
Availability:	In stock

Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Inc.
Marketing Office Readymoney Terrace, 167, Dr. Annie Besant Road, Worli, Mumbai 400 018, India Tel +91(22) 6123 3500 Fax +91(22) 2493 8826 www.uniphos-she.com	Factory P.O. Nahuli – 396 108 Tal. Umbergaon, Dist: Valsad, Gujarat, India Tel +91 9909994042 +91 7574839945 www.uniphos-she.com	2245 Texas Drive, Suite 300 Sugar Land, TX 77479 USA Tel +1 844.247.0450 orders.usa@uniphos-envirotronic.com www.uniphosamericas.com