



February 12, 2018

New Detector Tube from Uniphos Envirotronic Pvt. Ltd.

Description:	NO ₂ & NO
Part Number:	SNDNO-4L
Measuring Range:	2.5-200 ppm NO ₂ & 2.5-200 ppm NO
Tests per Box:	5
Number of Strokes:	1 stroke for 2.5-200 ppm of NO ₂ & NO; Two tubes are connected using a rubber tube and the air is drawn through both tubes simultaneously
Time per Stroke:	60 seconds
Discoloration:	White to yellowish-orange (on both tubes)
Shelf Life:	1 year
Applications/Use:	<ul style="list-style-type: none"> • Nitrogen dioxide (NO₂) is an intermediate in the manufacturing of nitric acid. • NO₂ is nitrating agent in the manufacture of chemical explosives & an oxidizer in rocket fuels. • The primary use for nitric oxide (NO) is an intermediate in the synthesis of nitric acid from ammonia. • Nitrogen oxides (NO & NO₂) are emissions gases from diesel powered trucks and heavy equipment. • NO₂ is a concern in diesel powered equipment used in underground mining.
Availability:	In stock

Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Inc.
Marketing Office Readymoney Terrace, 167, Dr. Annie Besant Road, Worli, Mumbai 400 018, India Tel +91(22) 6123 3500 Fax +91(22) 2493 8826 www.uniphos-she.com	Factory P.O. Nahuli – 396 108 Tal. Umbergaon, Dist: Valsad, Gujarat, India Tel +91 9909994042 +91 7574839945 www.uniphos-she.com	2245 Texas Drive, Suite 300 Sugar Land, TX 77479 USA Tel +1 844.247.0450 orders.usa@uniphos-envirotronic.com www.uniphosamericas.com