



February 12, 2018

New Detector Tube from Uniphos Envirotronic Pvt. Ltd.

Description:	NO2 in CO2
Part Number:	CCND-1H
Measuring Range:	0.1-6 ppm v/v
Tests per Box:	10
Sampling Time/ Volume	4.0 min / 1100 ml of CO2 gas
Flow Rate:	275 ml/min
Discoloration:	White to yellowish orange
Shelf Life:	1 year
Applications/Use:	<ul style="list-style-type: none"> • The measurement of NO2 impurities in compressed carbon dioxide (CO2) gas cylinders. • Carbon dioxide (CO2) is as an inert gas used in welding and fire extinguishers, as a pressurizing gas in air guns and oil recovery. • It is used to produce carbonated soft drinks and soda water. • Trace amounts of contaminants in CO2 used to carbonate soft drinks can have an adverse effect on the taste of the soft drink.
Availability:	In stock

Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Pvt. Ltd.	Uniphos Envirotronic Inc.
Marketing Office Readymoney Terrace, 167, Dr. Annie Besant Road, Worli, Mumbai 400 018, India Tel +91(22) 6123 3500 Fax +91(22) 2493 8826 www.uniphos-she.com	Factory P.O. Nahuli – 396 108 Tal. Umbergaon, Dist: Valsad, Gujarat, India Tel +91 9909994042 +91 7574839945 www.uniphos-she.com	2245 Texas Drive, Suite 300 Sugar Land, TX 77479 USA Tel +1 844.247.0450 orders.usa@uniphos-envirotronic.com www.uniphosamericas.com