



PRODUCT SPECIFICATION DATA SHEET

UNIPHOS 370(M)

KWIKALERT HYDROGEN CHLORIDE GAS MONITOR



| GAS RELATED SPECIFICATIONS | |
|----------------------------|--|
| Gas Detected | Hydrogen Chloride |
| Concentration Range | 0 – 20 PPM |
| Resolution | 0.1 PPM |
| Detection Principle | Electrochemical Sensor |
| Accuracy | Inherently +/- 2% (but also depends on the accuracy of the calibration gas & method) |
| Sampling | Diffusion Mode |

| DISPLAY & INDICATOR SPECIFICATIONS | |
|------------------------------------|---|
| Display | Backlit 8x2 Alphanumeric OLED Display Status LEDs |
| Function Keys | 4-keys for basic operation/setting & calibration |
| Electronic Alarm | 85db Audio Alarm, Visual LEDs |

| ELECTRONICS AND ELECTRICAL SPECIFICATIONS | | |
|---|--|--|
| Electronics | Micro-Controller based instrument | |
| Connectivity | Mini USB for PC connectivity | |
| Data Logging | Data logging facility for up to 3000 samples User settable data logging interval Records gas readings along with time stamping | |
| Power Source | 7.4 V Li-ion rechargeable battery pack | |

| PHYSICAL SPECIFICATIONS | |
|------------------------------------|--|
| Operating Temperature Range | 0 to 40 Degree Celsius |
| Operating Pressure | Ambient +/- 10% |
| Enclosure | ABS Plastic |
| Weight | 300 grams |
| Dimensions | H x W x D: 135 x 70 x 35 mm |
| Standard Accessories | Battery Charger, USB cable, Dust filter, and Calibration Cap |