

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Carbon Dioxide CO₂

TLV (TWA): 5000 ppm

TLV (STEL): 30,000 ppm

SCD-5

Non-Flammable

Specification:

Measurement Range	Extended	Standard	Extended
	150 - 300 ppm	300 - 5000 ppm	5000 - 10000 ppm
No. of Pump Strokes	4 (400 mL)	2 (200 mL)	1 (100 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	3.5 minutes per pump stroke (100 mL)		
Color Change	Blue → Off white		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	CO ₂ + NaOH → Na ₂ CO ₃ + H ₂ O		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Carbon Monoxide	3000	No	No effect
Ammonia	50000	No	No effect
Nitrogen dioxide	200	No	No effect
Sulphur dioxide	2050	+	
n-Hexane	1500	No	No effect
Toluene	400	No	No effect

Correction for Environmental Parameters:

Temperature (°C):	4	20	30	40
Temperature Correction Factor (TCF) *	0.9	1	1.1	1.2

Relative humidity	Not necessary between 10 - 90 %.
-------------------	----------------------------------

* Multiply the observed reading by the correction factor (VCFXTCF) to obtain the true concentration.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0720