

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Ethyl benzene

C₈H₁₀

SEB-4L

TLV (TWA): 20 ppm

TLV (STEL): ----

Flammable Range: 1- 6.7 %

Specification:

Measurement Range	Extended	Standard	Extended
	2.5 – 5 ppm	5 – 150 ppm	150 - 300 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	½ (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Brown		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	C ₈ H ₁₀ + I ₂ O ₅ + H ₂ SO ₄ → I ₂		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Benzene		+	Brown
Toluene		+	Brown
Xylene		+	Brown
n - Hexane	300	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0720