

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Mercaptans

R-SH

SEM-4M

TLV (TWA): 0.5 ppm

TLV (STEL): ----

Flammable Range: 3 - 18%

### Specification:

Measurement Range	Extended	Standard	Extended
	12.5 - 25 ppm	25 - 500 ppm	Do not extend
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	
Volume Correction Factor (VCF)*	0.5	1.0	
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	Yellow → Red		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated with Ethyl Mercaptan at 20°C (68°F) and 50% RH.		
Reaction Principle	$C_2H_5SH + HgCl_2 \rightarrow C_2H_5S.HgCl + HCl$ $HCl + Base \rightarrow Chloride$		
Relative standard deviation	± 10 -15 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Other Mercaptans		+	Pink
Phosphine		+	Pink
Hydrogen Sulphide		+	Pink
Arsine		+	Pink
Hydrogen Cyanide		+	Pink
Carbon Dioxide	10%	No	No effect
Ammonia	100	No	No effect
Sulphur Dioxide	30	No	No effect

### Other measurable compounds:

Compound	Correction Factor	No. of pump strokes	Measuring range
Methyl Mercaptan	1	1	25 - 500 ppm
t-Butyl Mercaptan	1	1	25 - 500 ppm

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.

**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbargaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108



Rev. 0920