


Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Ethylene Oxide



SEO-3

TLV (TWA): 1 ppm

TLV (STEL): ----

Flammable Range: 4-100%

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	1 – 100 ppm	Do not extend
No. of Pump Strokes		2 (200 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	2 minutes per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F) in Refrigerator		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle (Double Tube)	C ₂ H ₄ O + Oxidizer → HCHO (Pre-Treatment Tube) HCHO + (NH ₂ OH) ₃ .H ₃ PO ₄ → H ₃ PO ₄ H ₃ PO ₄ + Base → Phosphate (Detector Tube)		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Aldehydes		+	Pink
Ketones		+	Pink

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0720