

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Ethanol

## C<sub>2</sub>H<sub>5</sub>OH

## SET-5

TLV (TWA): 1000 ppm

TLV (STEL): -----

Flammable Range: 3.3-19%

### Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	100 – 5000 ppm	Do not extend
No. of Pump Strokes		1(100 mL)	
Volume Correction Factor (VCF)*		1	
Sampling Time	1.5 minutes per pump stroke (100mL)		
Color Change	Yellow → Light green		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	C <sub>2</sub> H <sub>5</sub> OH + Cr <sup>6+</sup> + H <sub>2</sub> SO <sub>4</sub> → Cr <sup>3+</sup>		
Relative standard deviation	± 10 – 15 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Alcohols		+	Light green
Esters		+	Light green
Ketones		+	Light green
Aromatic Hydrocarbons		+	Light green
Hydrogen Sulphide		+	Diffuse
Carbon Monoxide	1000	No	No Effect
Carbon Dioxide	5000	No	No Effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0620