

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Hydrogen Chloride HCl

SHC- 4

TLV (TWA): ----

TLV (Ceiling): 2 ppm

Non Flammable

Specification:

Measurement Range	Extended	Standard	Extended
	25 - 50 ppm	50 -1000 ppm	1000 - 2000 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	HCl + Base → Reaction product		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Chlorine		+	Pink
Hydrogen Fluoride		+	Diffuse
Ammonia	100	No	No effect
Nitrogen Dioxide	200	No	No effect
Hydrogen sulphide	100	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0820