

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Hydrogen Sulfide

H₂S

SHS-1

TLV (TWA): 1 ppm

TLV (STEL): 5 ppm

Flammable Range: 4-44%

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.5 - 10 ppm	Do not extend
No. of Pump Strokes	5 (500 mL)		
Volume Correction Factor (VCF)*	1.0		
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Brown		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$H_2S + Pb(CH_3COO)_2 \rightarrow PbS + 2CH_3COOH$		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Mercaptans	100	No	No effect
Sulphur dioxide	100	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0820