

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Hydrogen Sulfide



SHS-8M

TLV (TWA): 1 ppm

TLV (STEL): 5 ppm

Flammable Range: 4-44%

Specification:

Measurement Range	Extended	Standard	Extended
	0.25 – 0.5%	0.5 - 10%	10 - 20%
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	2.5 minutes per pump stroke (100 mL)		
Color Change	Blue → Black		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$H_2S + CuSO_4 \rightarrow CuS + H_2SO_4$		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (%)	Interference	Colour change / Comments
Ammonia	0.03	No	No effect
Nitrogen dioxide	0.02	No	No effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0820