

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

UDMH

TLV (TWA): 0.01 ppm

$(\text{CH}_3)_2\text{NNH}_2$

TLV (STEL): ----

SHY-1L

Flammable Range: 2 – 45 %

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.1 - 2 ppm	Do not extend
No. of Pump Strokes		5 (500 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Blue		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	$\text{C}_2\text{H}_8\text{N}_2 + \text{Acid} \rightarrow \text{Reaction product}$		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Methylamine		+	Blue
Hydrazine		+	Blue
Ethylamine		+	Blue

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0920