

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Nitrogen Oxides

NO_x

SNO-2M

TLV (TWA): 3 ppm (NO₂) & 25 ppm (NO)

Flammable Range: NA

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.5 - 15 ppm	Do not extend
No. of Pump Strokes		2 (200 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Orange		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	NO + Cr ⁶⁺ + H ₂ SO ₄ → NO ₂ NO ₂ + o - Tolidine → Orange reaction product		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Chlorine		+	Orange
Bromine		+	Orange
Hydrogen Sulphide	100	No	No Effect
Sulphur dioxide	200	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0920