

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Phosphine

PH₃

SPH-1M

TLV (TWA): 0.3 ppm

TLV (STEL): 1 ppm

Flammable Range: ~1.8 - 100%

Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.3 – 5 ppm	Do not extend
No. of Pump Strokes		3 (300 mL)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	2.0 minutes per pump stroke (100 mL)		
Color Change	Off White → Purple		
Shelf Life	2 years		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	PH ₃ + Gold compound → Reaction product		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Arsine		+	Purple
Hydrogen sulphide		+	Purple
Hydrogen selenide		+	Purple

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0920