

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Hydrogen Fluoride

HF

SHF-2

TLV (TWA): NA

TLV (Ceiling): 3 ppm

Not Flammable

### Specification:

Measurement Range	Extended	Standard	Extended
	Do not extend	0.5 - 30 ppm	1 - 60 ppm
No. of Pump Strokes		4 (400 mL)	2 (200 mL)
Volume Correction Factor (VCF)*		1.0	2.0
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Pale green → Purple		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	HF + Base → Reaction product		
Relative standard deviation	± 10 – 15 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Correction Factor	No. of pump strokes	Measuring range
Hydrogen Chloride		+	Purple
Chlorine		+	Purple
Hydrogen Sulphide	800	No	No effect
Sulphur dioxide	200	No	No effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).				
Relative humidity					
Relative Humidity at 20°C:	30%	40%	50%	60%	80%
Correction Factor (HCF)*:	0.5	0.7	1.0	1.2	1.7

\* Multiply the observed reading by the correction factors (VCFxHCF) to obtain the true concentration.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0820