

Part No. D5086814

Part No. (US): 497606

Performance :

Measurement Range	100 - 3000 ppm
Number of Strokes	5
Sampling Time	30 - 40 seconds per stroke
Relative Standard Deviation	±15 to 25 %
Colour Change	White → Blue

Reaction Principle :

$\text{CO}_2 + \text{N}_2 \text{H}_4 \rightarrow$ color change of an acid-base indicator.

Operating Conditions :

Detector tubes can be used without compensation of reading between 0 °C and 40 °C (32 °F and 104 °F) and between 10 % RH (0.5 mg/l at 0 °C [32 °F]) and 90 % RH (46 mg/l at 40 °C [104 °F]).

Interferences And Cross Sensitivities :

Compound	Interference
Hydrogen, Methane, Ethane, Propane, Butane, Carbon monoxide.	No interference
Higher saturated hydrocarbons (e.g.Hexanes, Octanes), Olefinic hydrocarbons (e.g. Ethylene), Aromatic hydrocarbons (e.g. Benzene) up to 1 vol%.	No interference
Sulphur dioxide, Hydrogen sulphide, Nitrogen dioxide, Hydrogen chloride and other acidic gases up to 100 ppm	No interference
Ammonia up to 100 ppm	No interference



TLV(TWA): 5000 ppm

TLV(STEL): 30,000 ppm

Flammable Range: Non Flammable