


# Ethyl Formate

C<sub>3</sub>H<sub>6</sub>O<sub>2</sub>

SEF-4M




## Specification :

Measurement Range	Extended	Standard	Extended
		20 – 500 ppm	
No. of Pump Strokes		2 (200 ml)	
Volume Correction Factor (VCF)*		1.0	
Sampling Time	3.0 minutes per pump stroke (100 ml)		
Color Change	Yellow → Pale Green		
Detection Limit	10 ppm (2 pump stroke)		
Shelf Life	1 year		
Relative standard deviation	± 10 – 15 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

## Reaction Principle :



## Possible Interferences :

Compound	Concentration (ppm)	Interference	Color Change / Comments
Alcohols	≥ 200	+	Pale green
Esters		+	Pale green
Ketones		+	Pale green
Aromatic hydrocarbons		+	Pale green

## Correction For Environmental Parameters :

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.

## Calibration Of The Tube :

Static gas dilution method.

TLV (TWA): ---

TLV (STEL): 100 ppm

Flammable Range: 2.8 – 16 %