

Specification:

	Extended	Standard	Extended
Measurement Range (SO2)	Do not extend	0.05-6%	6 - 12 %
No. of Pump Strokes		1 (100 ml)	0.5 (50 ml)
Volume Correction Factor (VCF)*		1	2
Sampling Time	2.0 minutes per pump stroke (100 ml)		
Color Change	Orange → Green with brown top		
Detection Limit	0.02%		
Shelf Life	2 years		
Relative standard deviation	± 10 – 15 %		

^{*} Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Reaction Principle:

 $CH_3OH + Cr^{6+} + H_2SO_4 \rightarrow Cr^{3+}$

Possible Interferences:

Compound	Concentration (ppm)	Interference	Color Change / Comments
Alcohols		+	Green with brown top
Carbon monoxide	≤1000	No	No Effect
Carbon dioxide	≤10%	No	No Effect
Acetone	≤1%	No	No Effect
Hydrogen Sulphide	≤ 100	No	No Effect

Correction For Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.

Calibration Of The Tube:

Static gas dilution method.

TLV (TWA): 200 ppm TLV (STEL): 250 ppm Flammable Range: 6-36.5%